

4

3

↓

2

1

PART NO. SEE TABLE

REVISIONS

LTR	DESCRIPTION	Drawing	DATE
A	RELEASE NEW PRODUCT	GARY	09/12/07
B	依客人要求修改螺絲孔	GARY	10/24/07

# CUSTOMER DRAWING

TABLE

007-01-00519	15 U" GOLD	LCP BLACK
007-01-00478	15 U" GOLD	PBT BLACK
007-01-00479	15 U" GOLD	PA9T BLACK
PART NO.	PLATED	PLASTIC&COLOR

NOTE:

1.MATERIAL :

BASE : HIGH TEMPERATURE THERMOPLASTIC UL94V-0,  
TERMINAL:COPPER ALLOY,THICKNESS = 0.30 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE  
SOLDER TAIL:150u"MIN MISTY TIN 50u" MIN NICKEL  
UNDERPLATE  
GOLD SPECIFICATION:SEE TABLE

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT  
CONTACT RESISTANCE: 30 MILLIOHMS MAX.  
INSULATION RESISTANCE: 1000 MEGOHMS MIN.  
DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.  
OPERATING TEMPERATURE: -40°C~+85°C4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC  
OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27  
JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN  
HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC  
EQUIPMENT(ROHS)

DIMENSION ARE  
MILLIMETERS  
TOLERANCES ARE :  
DECIMALS  
.X ± 0.20  
.XX ± 0.15  
ANGLE:  
X ± 3°

APPROVALS		DATE
DRAWN	GARY	10/24/07
CHECKED		
APPROVALS		

PART NO.			
007-01-00478/00479/00519			
TITLE:			
SATA 22P SOCKET 加長帶螺絲孔型			
SIZE	SCALE :	DRAWING NO.	REV.
mm	1 : 1	000527	B
ID NO.	XXXXXXXXXX		SHEET 1 OF 1

DESCRIPTION

QTY UNIT

DO NOT SCALE DRAWING

4

3

↑

2

1