

4

3

2

1

PART NO. SEE TABLE

REVISIONS

CUSTOMER DRAWING

LTR	DESCRIPTION	Drawing	DATE
A	ease for Manufacture Initial Rel	WITTY	10/06/07
B	3.90±0.15改為3.90 ^{+0.0} _{-0.15} 依規範增加尺寸的標註,修改彈片與實物相符	WITTY	04/11/08

D

TABLE

007-01-00513	30u"	PBT
007-01-00512	15u"	LCP
007-01-00511	15u"	PBT+30%G/F
007-01-00510	G/F	PBT+30%G/F
PART NO.	PLATED	BASE MATERIAL

C

B

NOTES:

1, MATERIAL:

HOUSING: SEE TABLE, UL94V-0, BLACK
 CONTACT: PHOSPHOR BRONZE T=0.30±0.01mm
 SPRING: SUS 301(ADD HARD) T=0.20±0.01mm

2, PLATING:

CONTACT: GOLD OVER 50u" MIN NICKEL
 UNDERPLATE, SOLDER TAIL 150u" MIN TIN OVER
 50u" MIN NICKEL UNDERPLATE

GOLD SPECIFICATION:

a, F/G; b, 15U"; c, 30U"

3. ELECTRICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.
 OPERATING TEMPERATURE: -20°C ~ +85°C

4. THE PRODUCT SHOULD BE GP COMPLIANCE

A

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS		APPROVALS		DATE	TITLE: SATA 7P SOCKET 180° ADD SPRING-2規格(ZX)
.X ± 0.20	.XX ± 0.15	DRAWN	WITTY	04/11/08	
ANGLE: X ± 1°		CHECKED			
		APPROVALS			
					SIZE mm
					SCALE : 1 : 1
					DRAWING NO. 000537
					REV. B
					ID NO. XXXXXXXXXX
					SHEET 1 OF 1

NO

DESCRIPTION

QTY

UNIT

DO NOT SCALE DRAWING

4

3

2

1