

4

3

2

1

PART NO. SEE TABLE 1

**CUSTOMER  
DRAWING**

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
C	CHANGE 2.00 TO 3.00	GARY	12/01/06
D	修改圖面與實物相符	GARY	02/27/07
E	修改塑膠壁厚	GARY	09/20/07

TABLE 1

020-01-00199	15 U" GOLD	PA BLACK
PART NO.	PLATED	COLOR FOR THE PLASTIC

NOTE:

1.MATERIAL :

HOUSING : HIGH TEMPERATURE THERMOPLASTIC ,UL94V-0

TERMINAL(MAX): COPPER ALLOY,THICKNESS = 0.30 mm

TERMINAL(MIN): COPPER ALLOY,THICKNESS = 0.25 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE

SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE

GOLD SPECIFICATION:SEE TABLE 1

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT

CONTACT RESISTANCE: 30 MILLIOHMS MAX.

INSULATION RESISTANCE: 1000 MEGOHMS MIN.

DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.

OPERATING TEMPERATURE: -40°C~+85°C

4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT(ROHS)

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.20 .XX ± 0.15  ANGLE: X ± 3'	APPROVALS		DATE	PART NO.
	DRAWN	GARY	09/20/07	020-01-00199
	CHECKED			TITLE:
	APPROVALS			SAS 29P Vertical 2 ROWS For Cable (SOLDER TAIL 3 IN 1)
SIZE	SCALE :	DRAWING NO.	REV.	
mm	1 : 1	000378	E	
D. NO.	XXXXXXXXXX		SHEET 1 OF 1	

DESCRIPTION

Q'TY UNIT

DO NOT SCALE DRAWING

4

3

2

1