

4

3

2

1

PART NO. SEE TABLE1

**CUSTOMER
DRAWING**

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
B	RELEASE NEW PRODUCT	GARY	05/24/07
C	修改圖面與實物相符	GARY	06/15/07
D	增加凸點	GARY	06/30/07
E	加高小7PIN	GARY	07/24/07

TABLE 1

020-01-00289	15 U" GOLD	PBT BLACK
020-01-00290	15 U" GOLD	PA9T BLACK
PART NO.	PLATED	COLOR FOR THE PLASTIC

NOTE:

1.MATERIAL :

HOUSING : HIGH TEMPERATURE THERMOPLASTIC ,UL94V-0
 TERMINAL(MAX): COPPER ALLOY,THICKNESS = 0.30 mm
 TERMINAL(MIN): COPPER ALLOY,THICKNESS = 0.25 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE
 SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
 GOLD SPECIFICATION:SEE TABLE 1

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.
 OPERATING TEMPERATURE: -40°C~+85°C

4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT(ROHS)

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.30 .XX ± 0.25 ANGLE: X ± 3°	APPROVALS		DATE	PART NO.
	DRAWN	GARY	07/24/07	020-01-00289/00290
	CHECKED			TITLE:
	APPROVALS			SAS 29P Vertical 2 ROWS R/A For Cable (SOLDER TAIL 3 IN 1)
	SIZE	SCALE :	DRAWING NO.	REV.
	mm	1 : 1	000489	E
	D. NO.	XXXXXXXXXX	SHEET 1 OF 1	

DESCRIPTION

Q'TY

UNIT

DO NOT SCALE DRAWING

4

3

2

1