

4 3 2 1

CUSTOMER DRAWING

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
AO	NEW	Jun.L	06/14'/07
B	ADD H=9.0 TYPE	Jun.L	10/16'/07

TABLE

PART NO.	CONTACT	DIM=A
020-01-00295	15u"	9.00
020-01-00296	30u"	9.00
020-01-00297	15u"	8.35
020-01-00298	30u"	8.35

RECOMMENDED PCB LAYOUT

NOTE: THICKNESS=1.6~3.0mm

- MATERIAL :
 HOUSING:High Temperature Thermoplastic,UL94V-0,COLOR:BLACK
 TERMINAL(max): Copper Alloy,THICKNESS=0.30mm
 TERMINAL(min): Copper Alloy,THICKNESS=0.25mm
 LATCH:SUS,THICK=0.30±0.01
- PLATING:
 CONTACT: Au OVER 50u" MIN NICKEL UNDERPLATE
 SOLDER TAIL: 100u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
- ELECTRONICAL SPECIFICATION:
 CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.
 OPERATING TEMPERATURE: -20°C~+85°C

SECTION A-A

DESCRIPTION

APPROVALS		DATE	PART NO.
DRAWN	Jun.L	10/16'/07	020-01-00295/00296 020-01-00297/00298
CHECKED			
APPROVALS			
TITLE: SAS 29P母頭魚眼孔兩柱加四個(W=2.7)魚叉			
SIZE	SCALE :	DRAWING NO.	REV.
mm	1 : 1	000497	B
ID NO.	XXXXXXXXXX	SHEET 1 OF 1	

D C B A

D C B A

NO 4 3 2 1