

4

3

2

1

PART NO. SEE TABLE1

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
A	RELEASE NEW PRODUCT	GARY	06/29/07
B	增加凸點	GARY	07/23/07
C	3.50改為3.60	GARY	09/05/07

CUSTOMER DRAWING

TABLE 1

020-01-00303	15 U" GOLD	PA9T BLACK
PART NO.	PLATED	COLOR FOR THE PLASTIC

NOTE:

1.MATERIAL :

HOUSING : HIGH TEMPERATURE THERMOPLASTIC ,UL94V-0
 TERMINAL(MAX): COPPER ALLOY,THICKNESS = 0.30 mm
 TERMINAL(MIN): COPPER ALLOY,THICKNESS = 0.25 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE
 SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
 GOLD SPECIFICATION:SEE TABLE 1

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.
 OPERATING TEMPERATURE: -40°C~+85°C

4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT(ROHS)

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.30 .XX ± 0.25 ANGLE: X ± 3°	APPROVALS		DATE	PART NO. 020-01-00303			
	DRAWN	GARY	09/05/07				
	CHECKED			TITLE: SAS 29P Vertical 2 ROWS For Cable (SOLDER TAIL 3 IN 1, 2, 3)			
	APPROVALS			SIZE SCALE : DRAWING NO. REV. mm 1 : 1 000500 C			
NO	DESCRIPTION	Q'TY	UNIT	DO NOT SCALE DRAWING	D. NO.	XXXXXXXXXX	SHEET 1 OF 1

4

3

2

1