



Mating Height Draw (Reference)

Contact Diminsion

N(PIN)	DIM.A	DIM.B	DIM.C	N(PIN)	DIM.A	DIM.B	DIM.C
16P	2.80	5.30	4.40	40P	7.60	10.10	9.20
20P	3.60	6.10	5.20	46P	8.80	11.30	10.40
24P	4.40	6.90	6.00	50P	9.60	12.10	11.20
30P	5.60	8.10	7.20	60P	11.60	14.10	13.20
32P	6.00	8.50	7.60	70P	13.60	16.10	15.20
34P	6.40	8.90	8.00	80P	15.60	18.10	17.20

How To Order
BF04-XXG-126

Height 1.26mm
G: Gold Flash
No. Of Contact
0.4mm B TO B FEMALE

Specifications

1. Current Rating : 0.3A AC/DC
2. Voltage Rating : 50V AC/DC
3. Contact Resistance : 40m ohm. max.
4. Insulation Resistance : 100M ohm. min.at 100V DC
5. Withstanding Voltage :100V AC for one minute
6. Operating Temperature Range : -25°C to +85°C

Material and Plating

- 1.Housing : LCP (Natural Color)UL94V-0
 - 2.Contact : Phosphor Bronze
 - 3.Plating : 3u" Gold Flash
- Number Of Connector:2500pcs/Reel

DRAWN: Jeremy Liu	GENERAL TOLERANCE: .X = ±0.2 .XX = ±0.15	B	16-Dec-2003	BF04-XXG-126	Jeremy Liu
		A	04-Sep-2003	Release	Jeremy Liu
CHECKED: Jerry Chen	UNIT: MM	REV	DATE	FILE	BY
	SCALE:15:1	DESCRIPTION: 0.4mm B TO B FEMALE 母座 1.26mm High			SIZE
APPROVAL: Mike Wu	SHEET: 1 / 1	PART NO: BF04-XXG-126 FEMALE 母座			A4
	PROJECTION:				